

| MODEL NUMBER | CAPACITY (pF) | PEAK TEST VOLTAGE (KV) | RF WORKING VOLT.(KV) | AMPS (RMS) MAX. | NOMINAL DIMENSIONS |          |             |          | WEIGHT (NOM.) |
|--------------|---------------|------------------------|----------------------|-----------------|--------------------|----------|-------------|----------|---------------|
|              |               |                        |                      |                 | INCHES             |          | MILLIMETERS |          |               |
|              |               |                        |                      |                 | LENGTH             | DIAMETER | LENGTH      | DIAMETER |               |
| CKT100/18/80 | 100± 5%       | 25                     | 18                   | 80              | 4.50               | 2.68 MAX | 114.3       | 68.0 MAX | 0.56 Kg       |
| CKT75/18/75  | 75± 5%        | 25                     | 18                   | 75              | 4.50               | 2.68 MAX | 114.3       | 68.0 MAX | 0.56 Kg       |
| CKT50/18/68  | 50± 10%       | 25                     | 18                   | 68              | 4.50               | 2.68 MAX | 114.3       | 68.0 MAX | 0.56 Kg       |
| CKT25/18/58  | 25± 10%       | 25                     | 18                   | 58              | 4.50               | 2.68 MAX | 114.3       | 68.0 MAX | 0.50 Kg       |

